

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Uni-Mould Tooling Gel-Coat
Type of product : Resin

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Coating

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Easy Composites Ltd
Unit 39, Park Hall Business Village, Stoke on Trent,
Staffordshire, ST3 5XA. United Kingdom.
T +44 (0) 1782 454499 (08:00 - 17:30hrs, Mon-Fri) - F +44 (0)1782 596868
sales@easycomposites.co.uk - www.easycomposites.co.uk

1.4. Emergency telephone number

Emergency number : ORFILA - 0033 1 45 42 59 59

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3	H226
Acute Tox. 4 (Inhalation:dust,mist)	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Repr. 2	H361
STOT RE 1	H372

Full text of H-statements: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Xn; R20
Xi; R36/37/38
R10
Xn; R48/20

Full text of R-phrases: see section 16

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) : Danger
Hazardous ingredients : Styrene
Hazard statements (CLP) : H226 - Flammable liquid and vapour
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled

Uni-Mould Tooling Gel-Coat

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Precautionary statements (CLP)	H361 - Suspected of damaging fertility or the unborn child H372 - Causes damage to organs through prolonged or repeated exposure P280 - Wear protective gloves, protective clothing, eye protection P241 - Use explosion-proof electrical equipment P271 - Use only outdoors or in a well-ventilated area P370+P378 - In case of fire: Use Water fog, foam, extinguishing powder, carbon dioxide (CO2) for extinction P264 - Wash hands thoroughly after handling P210 - Keep away from heat, hot surfaces, sparks, open flames. - No smoking
--------------------------------	--

2.3. Other hazards

Adverse physicochemical, human health and environmental effects	: Flammable liquid and vapour. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation.
---	--

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Styrene	(CAS No) 100-42-5 (EC no) 202-851-5 (EC index no) 601-026-00-0 (REACH-no) 01-2119457861-32	30 - 40	Repr.Cat.3; R63 Xn; R20 Xn; R48/20 Xi; R36/38 R10	Flam. Liq. 3, H226 Repr. 2, H361d Acute Tox. 4 (Inhalation), H332 STOT RE 1, H372 Skin Irrit. 2, H315 Eye Irrit. 2, H319
	(CAS No) 64742-95-6 (EC no) 265-199-0 (EC index no) 649-356-00-4 (REACH-no) 01-2119455851-35	< 1	Xn; R65 N; R51/53 R10 R67 R66 Xi; R37	Flam. Liq. 3, H226 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
ethanediol, ethylene glycol substance with a Community workplace exposure limit	(CAS No) 107-21-1 (EC no) 203-473-3 (EC index no) 603-027-00-1 (REACH-no) 01-2119472426-35	< 1	Xn; R22	Acute Tox. 4 (Oral), H302
xylene substance with a Community workplace exposure limit	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9 (REACH-no) 01-2119488216-32	< 1	R10 Xn; R20/21 Xi; R38	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315
ethylbenzene substance with a Community workplace exposure limit	(CAS No) 100-41-4 (EC no) 202-849-4 (EC index no) 601-023-00-4	< 1	F; R11 Xn; R20 Xn; R65 Xn; R48/20	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304
	(CAS No) 95-71-6 (EC no) 202-443-7	< 1	Xn; R22 Xi; R36/38 N; R50	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Acute 1, H400 (M=10)

Specific concentration limits:

Name	Product identifier	Specific concentration limits: DSD/DPD	Specific concentration limits: CLP
Styrene	(CAS No) 100-42-5 (EC no) 202-851-5 (EC index no) 601-026-00-0 (REACH-no) 01-2119457861-32	(C >= 12,5) Xn;R20 (C >= 12,5) Xi;R36/38	
xylene	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9 (REACH-no) 01-2119488216-32	(C >= 12,5) Xn;R20/21	

Full text of R- and H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
----------------------------	---

Uni-Mould Tooling Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after skin contact	: Irritation.
Symptoms/injuries after eye contact	: Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Use water spray or fog for cooling exposed containers. Prevent entry to sewers and public waters.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Do not breathe vapours. fume.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe fume. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed.

7.3. Specific end use(s)

No additional information available

Uni-Mould Tooling Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Styrene (100-42-5)		
United Kingdom	WEL STEL (mg/m ³)	1080 mg/m ³
United Kingdom	WEL STEL (ppm)	250 ppm
ethanediol, ethylene glycol (107-21-1)		
EU	IOELV TWA (mg/m ³)	246 mg/m ³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m ³)	492 mg/m ³
EU	IOELV STEL (ppm)	100 ppm
ethylbenzene (100-41-4)		
EU	Local name	Ethylbenzene
EU	IOELV TWA (mg/m ³)	442 mg/m ³
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (mg/m ³)	884 mg/m ³
EU	IOELV STEL (ppm)	200 ppm
EU	Notes	Skin
xylene (1330-20-7)		
EU	Local name	Xylene, mixed isomers, pure
EU	IOELV TWA (mg/m ³)	221 mg/m ³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m ³)	442 mg/m ³
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: Wear appropriate mask



Environmental exposure controls	: Avoid release to the environment.
---------------------------------	-------------------------------------

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Black.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 1 - 1,1
Solubility	: No data available

Uni-Mould Tooling Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Inhalation:dust,mist: Harmful if inhaled.

ATE CLP (dust,mist)	4,028 mg/l/4h
---------------------	---------------

Styrene (100-42-5)

LD50 oral	> 5000 mg/kg
LD50 dermal	> 5000 mg/kg

ethanediol, ethylene glycol (107-21-1)

LD50 oral rat	7712 mg/kg
LD50 dermal	> 3500 mg/kg mouse
LC50 inhalation rat (mg/l)	> 2,5 mg/l

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Styrene (100-42-5)

LC50 fish 1	4,02 mg/l
EC50 Daphnia 1	4,7 mg/l

ethanediol, ethylene glycol (107-21-1)

LC50 fish 1	72860 mg/l
EC50 Daphnia 1	> 100 mg/l
NOEC chronic fish	15380 mg/l

ethanediol, ethylene glycol (107-21-1)

NOEC chronic crustacea	8590 mg/l
------------------------	-----------

(95-71-6)

LC50 fish 1	0,09 mg/l (Pimephales promelas; 96h)
-------------	--------------------------------------

12.2. Persistence and degradability

ethanediol, ethylene glycol (107-21-1)

Biodegradation	90 - 100 %
----------------	------------

Uni-Mould Tooling Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available




SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information


In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA
14.1. UN number		
1866	1866	1866
14.2. UN proper shipping name		
RESIN SOLUTION	RESIN SOLUTION	Resin solution
Transport document description		
UN 1866 RESIN SOLUTION, 3, III, (D/E)	UN 1866 RESIN SOLUTION, 3, III	
14.3. Transport hazard class(es)		
3	3	3
		
14.4. Packing group		
III	III	III
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		

14.6. Special precautions for user

- Overland transport

Special provisions (ADR) : 640E
Transport category (ADR) : 3
Hazard identification number (Kemler No.) : 30
Orange plates :



Tunnel restriction code (ADR) : D/E
EAC code : •3YE

- Transport by sea

EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : A
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

- Air transport

PCA packing instructions (IATA) : 355
CAO packing instructions (IATA) : 366
ERG code (IATA) : 3L

Uni-Mould Tooling Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : Information in this safety data sheet is based on actual knowledge in our possession and our experience. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. It is the user's responsibility to take the mentioned precautionary measures and to ensure that this information is complete and sufficient for the use of this product.

Full text of R-, H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H361	Suspected of damaging fertility or the unborn child
H361d	Suspected of damaging the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life

Uni-Mould Tooling Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

H411	Toxic to aquatic life with long lasting effects
R10	Flammable
R11	Highly flammable
R20	Harmful by inhalation
R20/21	Harmful by inhalation and in contact with skin
R22	Harmful if swallowed
R36/37/38	Irritating to eyes, respiratory system and skin
R36/38	Irritating to eyes and skin
R37	Irritating to respiratory system
R38	Irritating to skin
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation
R50	Very toxic to aquatic organisms
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R63	Possible risk of harm to the unborn child
R65	Harmful: may cause lung damage if swallowed
R66	Repeated exposure may cause skin dryness or cracking
R67	Vapours may cause drowsiness and dizziness
F	Highly flammable
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product